(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 28 July 2005 (28.07.2005)

PCT

(10) International Publication Number WO 2005/069601 A1

(51) International Patent Classification7: H04N 3/15, 5/32

(21) International Application Number:

PCT/IB2005/050092

(22) International Filing Date: 7 January 2005 (07.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

04100073.8 12 January 2004 (12.01.2004) EP

(71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Steindamm 94, 20099 Hamburg (DE).


- (71) Applicant (for all designated States except DE, US): KONINKLIJKE PHILIPS ELECTRONICS N. V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (71) Applicant (for all designated States except US): FRAUN-HOFER GESELLSCHAFT ZUR FÖRDERUNG

DER ANGEWANDTEN FORSCHUNG E.V. [DE/DE]; Hansastr. 27 c, 80686 München (DE).

- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SUCH, Olaf [DE/DE]; Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE). LAUTER, Josef [DE/DE]; Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE). GNADE, Michael [DE/DE]; Uhlenbroicher Weg 1, 47269 Duisburg (DE). WEILER, Dirk [DE/DE]; Ringstrasse 174 b, 44627 Herne (DE). KEMNA, Armin [DE/DE]; Neustrasse 88, 47228 Duisburg (DE). VOGTMEIER, Gereon [DE/DE]; Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE). STEADMAN, Roger [ES/DE]; Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (74) Agents: VOLMER, Georg et al.; Philips Intellectual Property &, Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

[Continued on next page]

(54) Title: SEMICONDUCTOR-BASED IMAGE SENSOR



(57) Abstract: A detector arrangement and/or a semiconductor-based image sensor with a plurality of detector elements or image pixels is described, which each have an integrated SD- (Sigma Delta) Modulator (20 to 29) or an integrated SD-A/D-(Sigma Delta Analog/Digital) converter (20 to 30), as well as particularly such a detector arrangement and/or such an image sensor on the basis of a CMOS-semiconductor. Particularly on the basis of the differential version and/or the multi-phase structure of the SD modulator and the SD-A/D converter, a detector arrangement and/or an image sensor with specially high noise robustness, a high dynamic range and a lesser noise can be produced, so that this is particularly suitable for usage in Computer Tomography (CT) apparatus.



WO 2005/069601 A1

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.